TOTO®

WT151M / WT152M

DuoFit® In-Wall Tank System, 1.6GPF & 0.9GPF

FEATURES

- Dual-Max flushing system, low consumption (1.6GPF/6.0LPF & 0.9GPF/3.4LPF) Avg. flush 1.28GPF
- Adjustable 15"-19" mounting height
- Saves up to 9" of floor space compared to standard floor-mounted toilet
- Support up to 880lbs
- Commercial 2" x 6" or optional residential installation with 2" x 4" wall studs with waste outlet kit
- 1-pc blow molded polyethylene tank to prevent leaks
- 2" x 6" Polyethylene outlet included
- Pre-plumbed for optional Washlet® connection
- Complete with #01 Cotton bolt caps

MODELS

- WT151M - with Pex-C washlet supply line
- WT152M - with copper washlet supply line
- YT800#WH - White
- YT820#SS - Brushed Stainless Steel
- YT820#CP - Polished Chrome
- YT830#WH- Glass/White

Optional Outlets (sold separately)

- THU343 2" x 4" outlet HDPE & PVC
- THU335 2" x 6" outlet cast iron
- THU468 Washlet connection kit

- CT418F(G) Aquia® wall-hung toilet by TOTO (sold separately)




White


Brushed Stainless Steel or Polished Chrome


Glass/White

PRODUCT SPECIFICATION

This universal height, high-efficiency, dual flushing, in-wall tank system toilet shall be 1.6GPF & 0.9GPF. Requires TOTO toilet model CT418FG. In-Wall tank system shall be TOTO Model WT15_____M____.

CODES/STANDARDS

- Meets and exceeds
  - Carrier system: ASME A112.6.2
  - Tank trim: IAPMO PS50, CSA B125.3, ASSE1002
- Certifications: IAPMO(cUPC), and others
- Code compliance: UPC, IPC, NSPC, NPC Canada, and others

WT151M / WT152M

DuoFit™ In-Wall Tank System, 1.6GPF & 0.9 GPF

SPECIFICATIONS

• Water Use	1.6 GPF & 0.9GPF (6.0 LPF & 3.4LPF)
• Flush System	Dual-Max
• Min. Water Pressure	8 psi (static)
• Installation Height	15" to 19" (projected range)
• Warranty	One Year Limited Warranty
• Material	Various
• Shipping Weight	WT151M / WT152M - 38lbs.
• Shipping Dimensions	WT151M / WT152M 48" x 26-1/2" x 6"

INSTALLATION NOTES

Adequate structural bracing is required.

